

# RC3502HD-5211/6311



## H.264 Full HD Outdoor Fixed IP Dome Camera

- Full HD1080p @ 30fp
- 6311 Model fit with Remote Zoom/Focus Control (One Click AF)
- Video Compression: H.264, MJPEG
- True Day/Night and WDR
- Video Dual Stream, Two-way Audio with G.711
- MicroSD/SDHC Memory Card Slot
- ONVIF Support, PoE (IEEE 802.3af)
- Embedded VCA Technology Video Analytics
- Vandal Proof IK-10 / IP66 Protection Rating



### Specifications

| CAMERA                           |  |
|----------------------------------|--|
| <b>Model</b>                     | <b>RC3502HD-5211:</b> Vario focal lens<br><b>RC3502HD-6311:</b> Motorized Focus & Zoom lens  |
| <b>Image Sensor</b>              | -5211: 1/2.7" 1080p CMOS<br>-6311: SONY EXMOR 1/2.9" 1080p CMOS  |
| <b>Effective Pixels</b>          | 1920 x 1080  |
| <b>Scanning System</b>           | Progressive scanning   |
| <b>AGC Control</b>               | Auto, adjustable amplification level   |
| <b>Minimum Illumination</b>      | Color: 0.5 lux, F1.2 - B/W : 0.001Lux (DSS ON)   |
| <b>Lens /-5211 Model</b>         | Manual 3.0 - 9.0mm Vari-Focal, F1.2 - 360, DC Auto Iris  |
| <b>Lens /-6311 Model</b>         | 3.0 - 9.0mm Vari-Focal, F1.2-360, DC Auto Iris<br>Motorized Focus & Zoom Control - One Click Focus Function  |
| <b>Lens Angle of View</b>        | Wide approx: 93.0°(H) x 68.4°(V)<br>Tele approx: 31.7°(H) x 23.8°(V)   |
| <b>Shutter Time</b>              | 1/10.000s to 1/2s  |
| <b>Shutter Exposure Modes</b>    | Automatic - with configurable min. shutter speed<br>Manual - with configurable fixed shutter speed<br>Flicker-Control - 50/60Hz  |
| <b>Day &amp; Night Switching</b> | Auto/Manual (both switching level adjustable 1 ~ 64)<br>Removable IR Cut Filter  |
| <b>Image Settings</b>            | Configurable brightness, contrast, saturation, sharpness, vertical flip & horizontal mirror function   |
| <b>2D-DNR</b>                    | Configurable digital noise reduction 1 ~ 16  |
| <b>Wide Dynamic Range</b>        | -5211: Digital WDR<br>-6311: Up to 100dB Dynamic Range with WDR  |
| <b>Exposure Adjustment</b>       | +1.0, +0.6, +0.3, 0, -0.3, -0.6, -1.0 EV   |
| <b>White Balance</b>             | ATW1 / ATW2 / Push / Manual  |
| <b>DSS (Sens-up)</b>             | Configurable digital slow shutter 2X ~ 16X   |
| <b>Backlight Compensation</b>    | BLC On/Off (possible to designate zone)  |
| VIDEO                            |  |
| <b>Video Compression</b>         | H.264 Baseline, Main, High profile (MPEG-4 Part 10 / AVC), MJPEG (Motion JPEG)   |
| <b>Video Streaming</b>           | Dual Stream, Independent Configurable<br><b>H.264:</b> Controllable frame rate and image resolution, video stream bandwidth limitation (VBR/CBR)<br><b>MJPEG:</b> Controllable frame rate and image resolution, JPEG quality |
| <b>Resolutions</b>               | 1920x1080, 1280x720, 1120x630, 960x540, 800x450, 640x360, 480x270, 320x180   |

| VIDEO                                    |   |
|--|---|
| <b>Frame Rate</b>                        | H.264: Configurable up to max 30fps in all resolution*<br>MJPEG: Configurable up to max 30fps in all resolution*  |
| <b>Motion Detection</b>                  | Max. 8 zones with independent configuration of detection sensitivity and target object size   |
| <b>Burnt-in Text</b>                     | Time / Date / Name (Name up to 48 characters), flexible display position configuration  |
| <b>Privacy Mask Zones</b>                | 4 flexible configurable regions   |
| <b>Analogue Video</b>                    | NTSC/PAL (3 minutes, only for installation purpose)   |
| AUDIO                                    |   |
| <b>Audio input / output</b>              | Line-In: 0.178Vp-p, 10KΩ<br>Lineout: 2.26Vp-p, 10KΩ   |
| <b>Compression Format</b>                | G.711-uLaw  |
| NETWORK                                  |   |
| <b>Ethernet Standard</b>                 | 10 / 100 Base-T   |
| <b>Protocol</b>                          | QoS Layer 3 DiffServ, TCP/IP, UDP/IP, HTTP, RTSP, RTCP, RTP/UDP, RTP/TCP, mDNS, UPnP™, SMTP, DHCP, DNS, DynDNS, NTP, SNMPv1/v2c/v3(MIB-II), IGMP, ICMP, SSLv2/v3, TLSv1 |
| <b>Users Connection</b>                  | Live viewing for up to 10 clients   |
| <b>Security</b>                          | Multi-level access with password protection   |
| GENERAL                                  |   |
| <b>I/O Terminal</b>                      | 1x Alarm In - max 50mA@5VDC, TTL<br>1x Alarm Out - max 50mA@24VDC, TTL  |
| <b>Edge Storage</b>                      | 1x MicroSD/MicroSDHC card slot (card not included) (Recommend Class 6 and higher for HD recording)  |
| <b>Application Programming Interface</b> | Software Development Kit (SDK) available<br>ONVIF compliant (release V1.4.0.x or higher)  |
| <b>Approvals</b>                         | FCC, CE, KC, IP66, IK-10, RoHS  |
| ELECTRICAL                               |   |
| <b>Power Source</b>                      | 12V DC / PoE (IEEE 802.3af)   |
| <b>Power Consumption (Approx)</b>        | RC3502HD-5211: 14.16W @ DC 12V<br>RC3502HD-6311: 14W @ DC 12V   |
| ENVIROMENT                               |   |
| <b>Heater</b>                            | Heater Unit (Heater Function only with 12V-DC power)  |
| <b>Operation Temperature</b>             | DC12V: -40°C ~ 50°C (-40°F ~ 122°F)<br>PoE: 0°C ~ 50°C (32°F ~ 122°F)<br>Cold Start<br>DC12V: -20°C (-4°F) / PoE: 0°C (32°F)  |
| <b>Operating Humidity</b>                | Up to 85% RH, Non-condensing  |

\* If VCA is activate, frame rate is limit to max. 15fps@1080p. Limitations are based on V.1.6.0 firmware release and could be changed without notice

# RC3502HD-5211/6311

| MECHANICAL                                    |   |
|---|---|
| <b>Material</b>                               | Aluminum Die Casting, Anti-vandal bubble (PC)   |
| <b>Color</b>                                  | White   |
| <b>Dimension</b>                              | Housing: 155( Φ ) x 129(H) mm,<br>Dome: 100( Φ ) mm   |
| <b>Weight (Approx)</b>                        | 1.2kg (2.64 lbs)  |
| VIDEO CONTENT ANALYSIS (Included as Standard) |   |
| <b>High Performance</b>                       | Advanced tracking algorithm and low false alarm rate  |
| <b>Easy to Use</b>                            | Intuitive web browser interface   |
| <b>Detection Zones and Rules</b>              | Up to 40 zones (multi-segment polygons and lines)<br>60 VCA filter rules in total   |
| <b>On-screen Display</b>                      | Real-time display of tracking data and events via activeX plug-in in IE browser   |
| <b>Burnt in Annotation</b>                    | Allows the VCA annotation to be burnt into the raw video stream for displaying on third party application   |
| <b>Tamper Detection</b>                       | Recognize camera tampering via VCA detection (defocusing, lens covering, camera moving)   |
| <b>Event Actions</b>                          | Notification service via TCP/IP, HTTP, multicast or email text messages with snapshot, DO-contact, file upload on external FTP server, local SD memory card recording |

| VIDEO CONTENT ANALYSIS (Option extension License) |  |
|---|--|
| <b>Available License</b>                          | VCAdetectIP, VCAcountIP, VCAaccessIP, VCAsurveillanceIP, VCAadvancedIP   |
| <b>VCA Detection Filters</b>                      | Enter, Exit, Appear, Disappear, Stop, Direction, Dwell, Speed, Tailgating, Object Classification,  |
| <b>VCA Features</b>                               | <ul style="list-style-type: none"> <li>- Up to 20 Onscreen Counter Displays</li> <li>- Counting-Line for accuracy people and vehicle counting with local database and reporting service</li> <li>- VCA Event Metadata Streaming (RTSP/ RTP)</li> <li>- VCA calibration via 3D tools for right object size detection</li> <li>- Object classification allow to design different Object classes to include or exclude in VCA detection rule</li> </ul> |
| <b>Info VCA</b>                                   | Details regarding supported VCA filters and features of the different extension licenses find on 'Filter Matrix VCA License' document  |
| ACCESSORIES                                       |  |
| <b>Mounting Adapter</b>                           | FMB-3502 - Flush Mount Bracket<br>WMB-3000 - Wall Mount Bracket<br>CMB-3000 - Ceiling Mount Bracket<br>PMA-3000 - Pole Mount Adapter<br>CMA-3000 - Corner Mount Adapter  |

## Dimension

(Unit: mm)

