

OUTBREAK™

POWER OVER ETHERNET SPLITTER



POE splitter for delivering power via POE to non-POE network devices

Delivers 5V or 12V DC to non-POE devices from a POE network source by splitting data and power.

Simple POE splitter delivering clean power to non-POE devices

Fully IEEE 802.3af compliant and gigabit compatible

Steps down POE voltage (48V) to 5V or 12V DC

Compact unit with integral wall mount lugs

Ideal for non-POE wireless access points, IP phones, IP cameras

TECHNICAL SPECIFICATION

OUTBREAK™

POWER		
Input voltage	36V to 56V DC, receiving power on either data or spare pairs	
Input current	0.6A at 36V maximum load	
OUTPUT POWER		
OUTBREAK 5	12.5 watts at 5V DC	
OUTBREAK 12	12-14 watts at 12V DC	
	Output with short-circuit protection	
DC Output connector	Barrel connector 9mm x 2.5mm x 5.5mm, centre positive	
POE STANDARDS		IEEE 802.3af POE
ETHERNET INTERFACE		RJ45 Data and POE IN port RJ45 Data OUT port 10/100/1000 Base-T compatible
LEDS		
Status indicator	Green LED ON - Output OK	
PHYSICAL/ENVIRONMENTAL		
Dimensions	L 100mm (excluding flying lead) W 56mm H 28mm	
Weight	200g [7.0oz]	
Mounting	Integral wall-mount lugs	
Operating temperature	0°C to +40°C [32°F to 104°F]	
Relative humidity	5% to 90% non-condensing	
Compliance	CE, FCC, RoHS	
PRODUCT CODES		
	VOR-OB5	OUTBREAK 5V
	VOR-OB12	OUTBREAK 12V
		5V POE Splitter
		12V POE Splitter



Americas & Asia Sales :
Veracity USA Inc.
65 Harristown Road
Glen Rock
NJ 07452

USA
Tel: 1-800-679-1590
Fax: 1-800-679-0714
www.veracityglobal.com
sales@veracityusa.com

EMEA Sales :
Veracity UK Ltd
Prestwick International Aerospace Park
4 Dow Road
Prestwick
KA9 2TU
UK
Tel +44 (0) 1292 264967
Fax +44 (0) 845 528 1081
www.veracityglobal.com
sales@veracityuk.com